

# Premier Acoustic Product Datasheet



**Model: VS-15SB/VS-18SB**



## Description

Complementary sub bass system to VS range

Provides solid, controlled foundation for full range systems

Sound quality is extremely accurate so ideal for music reproduction

High power woofer delivers sustained, high output levels with minimum power compression

## Specification

MODEL	VS-15SB	VS-18SB
Frequency Response +/- 3dB	50Hz-400Hz	45Hz-400Hz
Sensitivity @ 1w/1m	97dB	97dB
Nominal Coverage – horizontal	-	-
Nominal Coverage – vertical	-	-
Input Power (W)		
Continuous	200	220
Music	400	440
Peak	800	880
Max SPL (peak)	123dB	124dB
Nominal Impedance	4ohm	4ohm
Dimensions (mm - Height x Width x Depth)	578 x 465 x 400	735 x 541 x 400
Shape	Rectangular	Rectangular
Weight	21.55kg	30.2kg
LF Driver Size (mm/ins)	380/15	440/18
Magnet Weight	1180g	1362g
Frame Material	Steel	Steel
HF Section Type	-	-
Coil Size (mm/ins)	65/2.5	75/3
System Box Frequency	40Hz	40Hz
Protect Type	-	-
Finish/Colour	Carpet/Black	Carpet/Black
Construction Materials	MDF	MDF
Grille	Black full	Black full
Stand Adaptor	-	-
Connectors In (power input from amplifier)	2 x ¼ " jack	2 x ¼ " jack

**Premier Acoustic Ltd, Unit 9, Sedgley Trading Estate, Sedgley Park,  
Prestwich, Manchester M25 9WS  
Tel: 0161 798 6336 Fax: 0161 798 6226  
VS15 18SB Page 1 of 1**