

Premier Acoustic Product Datasheet



**Model: Programme 50/Programme 52/
Programme 60**

Description

Compact 8 ohm system with high output and high efficiency

Smooth coverage and frequency response for ideal vocal reproduction and feedback isolation

Sophisticated crossover for smooth frequency and power response

Music/voice tone control switch (52 & 60)

PROTECH™ system limits overload and protects drivers against transient/peak conditions



Specification

| MODEL | Programme 50 | Programme 52 | Programme 60 |
|--|--------------------------|--------------------------|--------------------------------------|
| Frequency Response +/- 3dB | 40Hz-20kHz | 38Hz-20kHz | 35Hz-20kHz |
| Sensitivity @ 1w/1m | 89dB | 91dB | 91dB |
| Nominal Coverage – horizontal | 60° | 60° | 60° |
| Nominal Coverage – vertical | 60° | 60° | 60° |
| Input Power (W) | | | |
| Music | 80 | 100 | 200 |
| Peak | 160 | 200 | 400 |
| Max SPL (peak) | 111dB | 114dB | 118dB |
| Nominal Impedance | 8ohm | 8ohm | 8ohm |
| Dimensions (mm - Height x Width x Depth) | 303 x 196 x 203 | 500 x 196 x 203 | 674 x 246 x 300 |
| Shape | Trap | Trap | Trap |
| Weight (inc bracket) | 7.5kg | 13.5kg | 13.5kg |
| LF Driver Size (mm/ins) | 1 x 5.5" | 2 x 5.5" | 2 x 6.5" |
| HF Driver Type | 3/4 " titanium dome3/4 " | 3/4 " titanium dome3/4 " | 1 " comp. Driver |
| Crossover Point | 2.3kHz | 2.3kHz | 2.3kHz |
| Music and Voice Tone Switch | No | Yes | Yes |
| HF Driver Protect Type | Polyswitch | Bulb | Bulb |
| Finish/Colour | Black/White | Black/White | Black/White |
| Construction Materials | MDF | MDF | MDF |
| Grille | Full | Full | Full |
| Stand Adaptor | Yes | Yes | Yes |
| Connectors In (power input from amplifier) | Barrier strip | Barrier strip | Barrier strip + 2 x Speakon™ type |