

Premier Acoustic Product Datasheet



**Model: Programme 50T/
Programme 52T/Programme 60T**



Description

Compact 100v/70v line system with high output and high efficiency

Smooth coverage and frequency response for ideal vocal reproduction and feedback isolation

Sophisticated crossover for smooth frequency and power response

Music/voice tone control switch (52 & 60)

PROTECH™ system limits overload and protects drivers against transient/peak conditions

Specification

MODEL	Programme 50T	Programme 52T	Programme 60T
Frequency Response +/- 3dB	40Hz-20kHz	38Hz-20kHz	35Hz-20kHz
Sensitivity @ 1w/1m	89dB	91dB	91dB
Nominal Coverage – horizontal	60°	60°	60°
Nominal Coverage – vertical	60°	60°	60°
Input Power (W)	7.5, 15, 30, 60w	10, 20, 40, 80w	15, 30, 60, 120w
Max SPL (peak)	111dB	114dB	118dB
Nominal Impedance	Tap	Tap	Tap
Dimensions (mm - Height x Width x Depth)	303 x 196 x 203	500 x 196 x 203	674 x 246 x 300
Shape	Trap	Trap	Trap
Weight (inc bracket)	9kg	16kg	16kg
LF Driver Size (mm/ins)	1 x 5.5"	2 x 5.5"	2 x 6.5"
HF Driver Type	3/4 " titanium dome3/4 "	3/4 " titanium dome3/4 "	1 " comp. Driver
Crossover Point	2.3kHz	2.3kHz	2.3kHz
Music and Voice Tone Switch	No	Yes	Yes
HF Driver Protect Type	Polyswitch	Bulb	Bulb
Finish/Colour	Black/White	Black/White	Black/White
Construction Materials	MDF	MDF	MDF
Grille	Full	Full	Full
Stand Adaptor	Yes	Yes	Yes
Connectors In (power input from amplifier)	Barrier strip	Barrier strip	Barrier strip