

Premier Acoustic Product Datasheet



Model: Mobile-35 / Mobile-60



Description

Freestanding mixer amplifier available in a choice of 35 watt and 60 watt outputs.

Integral module slot enables a dedicated tuner, cassette player, tuner/cassette or digital message module to be fitted.

- Four audio inputs, each with individual attenuation (two are mic inputs, one is switchable between mic/line level and the fourth is at line level).
- The two mic inputs have vox priority over the other inputs and can also be switched so that one mic has priority over the other.
- Record out connections.
- Bass and treble controls.
- Output level LED meter.
- Telephone interface connections.
- 120/220/230/240 volt AC or 12 volt DC operation.

Specification

Model Number:	Mobile 35	Mobile 60
Rated output (RMS)	35w	60w
Output impedance	70V, 100V, 4Ω - 16Ω	
THD at 1kHz	<10% at 35w, <1% at 25w	<10% at 60w, <1% at 40w
Frequency response (±3dB)	150Hz – 18kHz	
Signal to noise ratio	Aux: >70dB, Mic: >60dB	
Input	Mic: -50dB/2kΩ balanced Aux: -20dB/60kΩ (Aux 1) balanced, -20dB/15kΩ (Aux 2) balanced Tape: 0dB/3kΩ unbalanced	
Weight (kg)	6	7
Dimensions (W x H x D) mm	375 x 88 x 260	
Power requirement	120V/220V/230V/240V AC 50/60Hz or 12V DC	